

## The Fixed Skylight By Vision AGI

### Detailed Description

Features:

Grade 6063-T6 Extruded Aluminium  
Fully Thermally Broken  
Polyester Powder Coating to Minimum 60 Microns  
Suitable for Marine / Coastal Environments  
Stainless Steel Concealed Fixings  
Air & Water Resistance 1050pa  
Tested in accordance with the CWCT Standard  
Wind Load Resistance 2.0kN/m<sup>2</sup>

Usage:

Suitable for all nominally flat roof constructions and coverings e.g. Single Ply PVC, Fiberglass, lead, copper, zinc and other standing seams and asphaltic material.

Suitable for Green / Sedum Roofs

Suitable for Pitched Roofs up to 45 Degrees



### Product Guidance

As Standard:

Stock / Standard Sizes (Non-standard sizes and shapes are available on request)

(mm)	Height	1000	1200	1400	1700	2000
<b>Width</b>						
1000		✓	✓	✓	✓	✓
1200		✓	✓	✓	✓	✓
1400		✓	✓	✓	✓	✓
1700		✓	✓	✓	✓	✓
2200		✓	✓	✓	✓	✓

*NB: These are external kerb sizes.*

*Internal finished sizes; minus 200mm from above Width & Height dimensions*



Glazing Details:

6 mm Toughened Outer  
20 mm Warm Edge Spacer with 90% Argon Cavity  
6mm Toughened Low-e Inner

Glass Centre Pane U-Value 1.1W/m<sup>2</sup>K

Colour:

Internal – Ral 9010 Mat  
External – Ral 7015 Mat

Seals:

Structural & Weather Seal – Low Modulus Silicone Sealant  
EPDM – UV & Water Resistant

Upstand:

To suit an overall finished Upstand of 100mm. Upstand by Vision AGI if required

Warranty:

1 Year offered as standard.  
Extended warranty available as below, upon registration.

Glazing 10 Years  
Powder Coating 10 Years  
Mechanical Components 1 Year

**Options**

Size:

Non-standard sizes and shapes are available on request.  
Any Single Pane Size up to 6000mm x 3000mm

Colour:

Any RAL or BS colour can be specified  
Anodised options

Glazing Details:

Enhanced glazing specifications incorporating thermal, acoustic, security, light transmission, solar gain, Class 2 Maintenance and decorative options are available, please contact manufacturer for details.

Frame Material:

Different material specifications stainless steel cladding etc are available please contact manufacturer for details.



Electric Actuation:  
See Opening Range

### Product Specification

Manufacturer:

Name: Vision AGI Ltd  
Web: [www.visionagi.co.uk](http://www.visionagi.co.uk)  
Email: [info@visionagi.co.uk](mailto:info@visionagi.co.uk)  
Tel: +44 (0)1245 392 108  
Address: Vision AGI Ltd, Queens Business Park, Wilbraham Road, Fulbourn, Cambridge, CB21 5GT  
Product reference: The Fixed Skylight

### Other Rooflights in the Range

Opening Roof Window – Manual  
Opening Roof Window – Electric  
Walk On Floorlight – (Internal Use)  
Walk On Rooflight – (External Use)  
Access Hatch Roof Window - Manual  
Access Hatch Roof Window – Electric  
Pyramid Rooflight  
Pyramid Rooflight – Manual  
Pyramid Rooflight - Electric  
Lantern Rooflight  
Lantern Rooflight - Manual  
Lantern Rooflight - Electric