

The Pyramid & Lantern Rooflights - Opening By Vision AGI

Detailed Description

Features:

Grade 6063-T6 Extruded Aluminium
Fully Thermally Broken
Polyester Powder Coating to Minimum 60 Microns

Suitable for Marine / Coastal Environments
Stainless Steel Concealed Fixings
Tested in accordance with the CWCT Standard
Air & Water Resistance 1050pa
Wind Load Resistance 2.0kN/m²



Usage:

Suitable for all nominally flat roof constructions and coverings e.g. Single Ply PVC, Fiberglass, lead, copper, zinc and other standing seams and asphaltic material.

Suitable for Green / Sedum Roofs

Product Guidance

As Standard:

Stock / Standard Sizes **Electric** Operation (Non-standard sizes and shapes are available on request)

(mm)	Height	1000	1200	1400	1500	1700	2000
Width							
1000		✓	✓	✓	✓	✓	✓
1200		✓	✓	✓	✓	✓	✓
1400		✓	✓	✓	✓	✓	✓
1500		✓	✓	✓	✓	✓	✓
1700		✓	✓	✓	✓	✓	✓
2000		✓	✓	✓	✓	✓	✓
2200		✓	✓	✓	✓	✓	✓



As Standard:

Stock / Standard Sizes **Manual** Operation (Non-standard sizes and shapes are available on request)

(mm)	Height	1000	1200	1400
Width				
1000		✓	✓	✓
1200		✓	✓	✓
1400		✓	✓	✓

NB: These are external kerb sizes.

Internal finished sizes; minus 200mm from above Width & Height dimensions

Glazing Details:

4mm Toughened Outer

20 mm Warm Edge Spacer with 90% Argon Cavity

4mm Toughened Low-e Inner

Glass Centre Pane U-Value 1.1W/m²K

Colour:

Internal – Ral 9010 Mat

External – Ral 7015 Mat

Seals:

Structural & Weather Seal – Low Modulus Silicone Sealant

EPDM – UV & Water Resistant

Upstand:

To suit an overall finished Upstand of 100mm. Upstand by Vision AGI if required

Warranty:

1 Year offered as standard.

Extended warranty available as below, upon registration.

Glazing 10 Years

Powder Coating 10 Years

Mechanical Components 1 Year



Options

Operation:

Manual or Electric, Wind, Rain & Temperature Sensors for auto-closing.
Remote Control

Size:

Non-standard sizes and shapes are available on request.

Colour:

Any RAL or BS colour can be specified
Anodised options

Glazing Details:

Enhanced glazing specifications incorporating thermal, acoustic, security, light transmission, solar gain, Class 2 Safety and decorative options are available, please contact manufacturer for details.

Frame Material:

Different material specifications stainless steel cladding etc are available please contact manufacturer for details.



Product Specification

Manufacturer:

Name: Vision AGI Ltd

Web: www.visionagi.co.uk

Email: info@visionagi.co.uk

Tel: +44 (0)1245 392 108

Address: Vision AGI Ltd, Queens Business Park, Wilbraham Road, Fulbourn, Cambridge, CB21 5GT

Product reference: The Pyramid & Lantern Rooflights - Opening

Other Rooflights in the Range

Fixed Rooflight

Opening Roof Window – Manual

Opening Roof Window – Electric

Access Hatch Roof Window – Manual

Access Hatch Roof Window – Electric

Walk On Floorlight – (Internal Use)

Walk On Rooflight – (External Use)

Pyramid Rooflight

Lantern Rooflight